



Echo 137

It is a well-known fact that all good things come from above. This is particularly true for Echo. Regent's new downlight is a delight even before being switched on. The installation of the lightweight is a matter of seconds and feasible completely tool-

free. The luminance of Echo is positively influenced by both mixing chamber and diffusion disc. The result: a pleasantly soft lighting experience which even sensitive eyes will find enjoyable, yet without compromising efficiency.

FEATURES

- Glare-free light thanks to highly precise light conduction
- High luminous efficiency
- Passive cooling
- Quick and tool-free mounting
- Lightweight system suitable for all ceiling types
- Streamlined design makes for perfect integration into ceiling architecture

TECHNICAL DATA

System power	14 W
Luminous flux of luminaire	1150 lm, 1400 lm, 1450 lm
Colour temperature	3000 K, 4000 K
Colour Rendering Index (CRI)	R _a ≥ 90
Maintained luminous flux	L80 (B50) 50'000 h
Protection class	I
Ingress Protection	IP20/IP44 from below when mounted in closed ceilings

SPECIFICATIONS

- Downlight with pleasantly homogeneous luminance levels
- Ceiling cut out 137 mm
- Aluminium-coated or white reflector
- Tool-free assembly of accessories
- DALI
- Operating unit included in delivery

APPLICATION AREAS

Retail & Hospitality: retail spaces, presentation of merchandise/key locations, restaurants, hotels, art & culture establishments







IP20
IP44

230V



0.5m 850°C


1

A

B

C
ECHO 137 LED

System power	Luminous flux of luminaire	Colour temperature	Notes	Unified Glare Rating	Emergency unit	Ref. n°
14 W	1450 lm	4000 K	reflector silver			1 A 1001.1900
14 W	1400 lm	3000 K	reflector silver			1 A 1001.1892
14 W	1150 lm	4000 K	reflector white			1 B 1001.2475
14 W	1150 lm	3000 K	reflector white			1 B 1001.2467
14 W	1450 lm	4000 K	reflector silver		with emergency unit	1 A 1008.8748
14 W	1400 lm	3000 K	reflector silver		with emergency unit	1 A 1008.8742
14 W	1150 lm	4000 K	reflector white		with emergency unit	1 B 1008.8936
14 W	1450 lm	4000 K	reflector silver	UGR ≤ 19		1 C 1001.1916
14 W	1400 lm	3000 K	reflector silver	UGR ≤ 19		1 C 1001.1908
14 W	1450 lm	4000 K	reflector silver	UGR ≤ 19	with emergency unit	1 C 1008.8772
14 W	1400 lm	3000 K	reflector silver	UGR ≤ 19	with emergency unit	1 C 1008.8758


COVER RING ECHO 137 LED

clear

Farbe	Notes	Ref. n°
white	IP44 from below, in case of closed ceilings	1001.2400
silber	IP44 from below, in case of closed ceilings	1001.2362
white	IP55 from below, in case of closed ceilings	1001.2402
silber	IP55 from below, in case of closed ceilings	1001.2364


COVER RING ECHO 137 LED

matt

Farbe	Notes	Ref. n°
white	IP55 from below, in case of closed ceilings	1001.2401
silber	IP55 from below, in case of closed ceilings	1001.2363



COVER RING ECHO 137 LED

Wallwasher

Farbe	Notes	Ref. n°
white	for reflector, wide beam	1001.2419
silber	for reflector, wide beam	1001.2417
white	for reflector, medium beam	1001.2428
silber	for reflector, medium beam	1001.2426


RING ECHO 137 LED

Notes	Ref. n°
for ceiling reinforcement	1001.2414


EMBEDDING HOUSING B.BOX

Notes	Ref. n°
in steel, sendzimized	1001.2266