

Echo 260

It is a well-known fact that all good things come from above. This is particularly true for Echo. Regent's new downlight is a delight even before being switched on. The installation of the lightweight is a matter of seconds and feasible completely tool-

free. The luminance of Echo is positively influenced by both mixing chamber and diffusion disc. The result: a pleasantly soft lighting experience which even sensitive eyes will find enjoyable, yet without compromising efficiency.

FEATURES

- Glare-free light thanks to highly precise light conduction
- High luminous efficiency
- Passive cooling
- Quick and tool-free mounting
- Lightweight system suitable for all ceiling types
- Streamlined design makes for perfect integration into ceiling architecture

TECHNICAL DATA

System power	31 W, 33 W, 34 W
Luminous flux of luminaire	1150 lm, 1400 lm, 1450 lm
Colour temperature	3700 K, 3800 K, 4000 K
Colour Rendering Index (CRI)	R _a ≥ 90
Maintained luminous flux	L80 (B50) 50'000 h
Protection class	I
Ingress Protection	IP20/IP44 from below when mounted in closed ceilings

SPECIFICATIONS

- Downlight with pleasantly homogeneous luminance levels
- Ceiling cut out 260 mm
- Aluminium-coated or white reflector
- Tool-free assembly of accessories
- DALI
- Operating unit included in delivery

APPLICATION AREAS

Retail & Hospitality: retail spaces, presentation of merchandise/key locations, restaurants, hotels, art & culture establishments






 IP20
 IP44

230V



0.5m

850°C



1

A

B

C

ECHO 260 LED

System power	Luminous flux of luminaire	Colour temperature	Notes	Unified Glare Rating	Emergency unit	Ref. n°
34 W	4000 lm	4000 K	reflector silver			1 A 1001.1971
34 W	3800 lm	3000 K	reflector silver			1 A 1001.1963
34 W	4000 lm	4000 K	reflector silver		with emergency unit	1 A 1008.8822
34 W	3700 lm	4000 K	reflector white			1 B 1001.2512
34 W	3500 lm	3000 K	reflector white			1 B 1001.2504
34 W	3700 lm	4000 K	reflector white		with emergency unit	1 B 1008.8955
34 W	4000 lm	4000 K	reflector silver	UGR ≤ 19		1 C 1001.1987
31 W	3800 lm	3000 K	reflector silver	UGR ≤ 19		1 C 1001.1979
34 W	4000 lm	4000 K	reflector silver	UGR ≤ 19	with emergency unit	1 C 1008.8842
33 W	3800 lm	3000 K	reflector silver	UGR ≤ 19	with emergency unit	1 C 1008.8830



COVER RING ECHO 260 LED

clear

Farbe	Notes	Ref. n°
white	IP44 from below, in case of closed ceilings	1001.2406
silber	IP44 from below, in case of closed ceilings	1001.2368
white	IP55 from below, in case of closed ceilings	1001.2408
silber	IP55 from below, in case of closed ceilings	1001.2370



COVER RING ECHO 260 LED


matt

Farbe	Notes	Ref. n°
white	IP55 from below, in case of closed ceilings	1001.2407
silber	IP55 from below, in case of closed ceilings	1001.2369



RING ECHO 260 LED

Notes	Ref. n°
for ceiling reinforcement	1001.2416



EMBEDDING HOUSING B.BOX

Notes	Ref. n°
in steel, sendzimized	1001.2271