



## Tweak

Every range of luminaires aims to feature a clear and consistent formal language. The surface-mounted wall version of Tweak combines all the advantages of free-standing luminaires – guaranteeing the same design, the same materials and the same high-quality and highly efficient lighting. Just without a stand.

**Elegant and  
efficient even  
without a stand.**

### FEATURES

Design luminaire with microprismatic optics for application in offices, aligns with the Tweak free-standing luminaire	
High luminous efficiency of up to 148 lm/W	
Direct and indirect lighting	
SensoDim® 2 presence detector and daylight sensor	
CLD optics for an especially even spread of light	
UGR ≤ 16 especially suitable for demanding visual tasks (pursuant to EN/ SN 12464-1)	
Die-cast aluminium housing	
Minergie	

### TECHNICAL DATA

System power	40 W
Luminous flux of luminaire	5600 lm, 5900 lm
Colour temperature	3000 K, 4000 K
Colour Rendering Index (CRI)	R <sub>a</sub> ≥ 80
Maintained luminous flux	L80 (B50) 50'000h
Protection class	I
Ingress Protection	IP20

### SPECIFICATIONS



Colours: white, silver
3000 K or 4000 K
dimnable digital DALI or SensoDim
Operating unit integrated
Also available as freestanding luminaire

### APPLICATION AREAS

**Office & Education:** offices, meeting rooms, reception rooms, staff training facilities, waiting rooms, libraries



IP20 230V 650°C



#### WALL MOUNTED LUMINAIRE TWEAK CLD LED

System power	Luminous flux of luminaire	Colour temperature	Colour	Light control	Ref. n°
40 W	5900 lm	4000 K	white	Sensodim	2000.9622
40 W	5900 lm	4000 K	white	DALI	2000.9617
40 W	5600 lm	3000 K	white	Sensodim	2001.1145
40 W	5600 lm	3000 K	white	DALI	2001.1144
40 W	5900 lm	4000 K	silver	Sensodim	2001.1143
40 W	5900 lm	4000 K	silver	DALI	2001.1141
40 W	5600 lm	3000 K	silver	Sensodim	2001.1142
40 W	5600 lm	3000 K	silver	DALI	2001.1140