



# CLIFF

Cliff impressively accentuates the main features of the room and embodies an expressive lighting solution. This pendant luminaire stands out thanks to its ultra-modern lighting technology that makes the room shine in a soft, homogeneous light. There's also something special about Cliff's appearance: slim and cylindrical, this elegant luminaire exudes a simple lightness and dynamism that lends a very special atmosphere to any environment. Cliff is available in three different lengths, thus offering plenty of scope for creative lighting design and a range of combination options. As a light source and decorative design element, this luminaire is sure to attract attention.

## FEATURES

- Elegant and timeless pendant luminaire
- The product range comprises 3 different sizes, 3 different degrees of luminous flux, 2 colour temperatures, and luminaire housings in a choice of 2 colour finishes
- Homogeneous illumination
- Simple cylindrical design
- Excellent colour rendering: CRI  $\geq 90$

## SPECIFICATIONS

- 3 lengths for a creative setup
- Luminaire housing made of aluminium
- Beam angle 24°
- Colour temperatures: 3000 K, 4000 K
- Integral electronic control gear, ON/OFF or DALI with mounting Canopy
- Luminaire always in one colour: luminaire housing + cable + canopy each in white and black

## TECHNICAL DATA





System power	12 W, 19 W
Luminous flux of luminaire	800 lm – 1300 lm
Colour temperature	3000 K, 4000 K
Colour Rendering Index [CRI]	Ra $\geq 90$
Maintained luminous flux	L70 [B50] 50'000h
Protection class	I
Ingress Protection	IP20
Photobiological safety	Risk group 1, low risk

## APPLICATION AREAS

- Retail & Hospitality:** lobbies, hotels, corridors, museums, exhibition spaces, galleries, restaurants, cafés
- Office & Education:** reception rooms, libraries
- Home & Living:** Dining and living areas



230V IP20 IK05  $\varnothing 0.5m$  650°C **A+**


**1**

**2**

**3**


## PENDANT LUMINAIRE CLIFF

System power	Luminous flux of luminaire	Colour temperature	Colour	Light control	Notes	Ref. n°
300 mm	12 W	850 lm	4000 K	white	DALI	<b>1</b> 2004.7987
300 mm	12 W	850 lm	4000 K	white	ON/OFF	<b>1</b> 2004.7986
300 mm	12 W	850 lm	4000 K	black	DALI	<b>1</b> 2004.7989
300 mm	12 W	850 lm	4000 K	black	ON/OFF	<b>1</b> 2004.7988
300 mm	12 W	800 lm	3000 K	white	DALI	<b>1</b> 2004.7983
300 mm	12 W	800 lm	3000 K	white	ON/OFF	<b>1</b> 2004.7982
300 mm	12 W	800 lm	3000 K	black	DALI	<b>1</b> 2004.7985
300 mm	12 W	800 lm	3000 K	black	ON/OFF	<b>1</b> 2004.7984
300 mm	19 W	1300 lm	4000 K	white	DALI	<b>1</b> 2004.7995
300 mm	19 W	1300 lm	4000 K	white	ON/OFF	<b>1</b> 2004.7994
300 mm	19 W	1300 lm	4000 K	black	DALI	<b>1</b> 2004.7997
300 mm	19 W	1300 lm	4000 K	black	ON/OFF	<b>1</b> 2004.7996
300 mm	19 W	1230 lm	3000 K	white	DALI	<b>1</b> 2004.7991
300 mm	19 W	1230 lm	3000 K	white	ON/OFF	<b>1</b> 2004.7990
300 mm	19 W	1230 lm	3000 K	black	DALI	<b>1</b> 2004.7993
300 mm	19 W	1230 lm	3000 K	black	ON/OFF	<b>1</b> 2004.7992
450 mm	12 W	850 lm	4000 K	white	DALI	<b>2</b> 2004.8003
450 mm	12 W	850 lm	4000 K	white	ON/OFF	<b>2</b> 2004.8002
450 mm	12 W	850 lm	4000 K	black	DALI	<b>2</b> 2004.8005
450 mm	12 W	850 lm	4000 K	black	ON/OFF	<b>2</b> 2004.8004
450 mm	12 W	800 lm	3000 K	white	DALI	<b>2</b> 2004.7999
450 mm	12 W	800 lm	3000 K	white	ON/OFF	<b>2</b> 2004.7998
450 mm	12 W	800 lm	3000 K	black	DALI	<b>2</b> 2004.8001
450 mm	12 W	800 lm	3000 K	black	ON/OFF	<b>2</b> 2004.8000
450 mm	19 W	1300 lm	4000 K	white	DALI	<b>2</b> 2004.8011
450 mm	19 W	1300 lm	4000 K	white	ON/OFF	<b>2</b> 2004.8010
450 mm	19 W	1300 lm	4000 K	black	DALI	<b>2</b> 2004.8013
450 mm	19 W	1300 lm	4000 K	black	ON/OFF	<b>2</b> 2004.8012
450 mm	19 W	1230 lm	3000 K	white	DALI	<b>2</b> 2004.8007
450 mm	19 W	1230 lm	3000 K	white	ON/OFF	<b>2</b> 2004.8006
450 mm	19 W	1230 lm	3000 K	black	DALI	<b>2</b> 2004.8009
450 mm	19 W	1230 lm	3000 K	black	ON/OFF	<b>2</b> 2004.8008
600 mm	12 W	850 lm	4000 K	white	DALI	<b>3</b> 2004.8019
600 mm	12 W	850 lm	4000 K	white	ON/OFF	<b>3</b> 2004.8018
600 mm	12 W	850 lm	4000 K	black	DALI	<b>3</b> 2004.8021
600 mm	12 W	850 lm	4000 K	black	ON/OFF	<b>3</b> 2004.8020
600 mm	12 W	800 lm	3000 K	white	DALI	<b>3</b> 2004.8015
600 mm	12 W	800 lm	3000 K	white	ON/OFF	<b>3</b> 2004.8014
600 mm	12 W	800 lm	3000 K	black	DALI	<b>3</b> 2004.8017
600 mm	12 W	800 lm	3000 K	black	ON/OFF	<b>3</b> 2004.8016

System power	Luminous flux of luminaire	Colour temperature	Colour	Light control	Notes	Ref. n°
600 mm	19 W	1300 lm	4000 K	white	DALI	<b>3</b> 2004.8027
600 mm	19 W	1300 lm	4000 K	white	ON/OFF	<b>3</b> 2004.8026
600 mm	19 W	1300 lm	4000 K	black	DALI	<b>3</b> 2004.8029
600 mm	19 W	1300 lm	4000 K	black	ON/OFF	<b>3</b> 2004.8028
600 mm	19 W	1230 lm	3000 K	white	DALI	<b>3</b> 2004.8023
600 mm	19 W	1230 lm	3000 K	white	ON/OFF	<b>3</b> 2004.8022
600 mm	19 W	1230 lm	3000 K	black	DALI	<b>3</b> 2004.8025
600 mm	19 W	1230 lm	3000 K	black	ON/OFF	<b>3</b> 2004.8024