



MILANO SLIM

MILANO SLIM is total light. 360 degree office light. Light that radiates in all its forms, directly, indirectly and laterally. Light which spreads beautifully outwards, distilled and refined by the frosted diffuser design. Easily mounted, full of features but free of glare, it can grace any office.

FEATURES

- Cylindrical diffuser just 58 mm, timeless design
- Direct-indirect light emission, omni-directional
- 2 optics, new: suitable for application in offices thanks to microprismatic C-LED optics. Diffuser omnidirectional
- Standard-compliant C-LED optics according to EN 12464-1 ensure perfect glare control and light suitable for office use
- Suitable for application in offices thanks to microprismatic C-LED optics with a $UGR < 16$; $L_{max} \geq 65^\circ \leq 3000 \text{ cd/m}^2$
- Diffuser made of high-grade plastic, attractive
- Extremely homogenous omnidirectional illumination
- Highly Efficient state-of-the-art LEDs, up to 173 lm/W
- LED board and optics replaceable

SPECIFICATIONS

- Luminaire for mounting on walls and ceiling, and for pendant mounting
- Diameter diffuser: 430 mm, 530 mm, 680 mm
- Pendant tube 1 m long as standard; can be shortened on site
- C-LED optics consisting of an inserted microprismatic plate in a transparent diffuser
- Pendant tube with ball and socket joint, self-adjusting up to 20°
- Other types of pendant possible thanks to accessories (3 m can be shortened on site, surface mounted and pendant luminaire)
- Operating unit integrated
- Suitable for emergency lighting (DC-compatible)
- Ceiling and wall mounted luminaire available with emergency unit
- Colour temperature can be adjusted individually with the Tunable White technology
- Light control: DALI or MyLights Remote Casambi

TECHNICAL DATA

System power	13 W – 69 W
Luminous flux of luminaire	1720 lm – 10'700 lm
Colour temperature	3000 K, 4000 K, 2700-6500 K
Colour Rendering Index [CRI]	$Ra \geq 80$
Maintained luminous flux	L80 50'000 h
Protection class	I
Ingress Protection	IP40
Photobiological safety	risk group 0, no risk





APPLICATION AREAS

- Office & Education:** classrooms, meeting rooms, offices, reception rooms, cafeterias, foyers and lobbies, corridors
- Retail & Hospitality:** hotels, reception areas, circulation zones



IP40 IK04 650°C




1

2

3


CEILING AND WALL MOUNTED LUMINAIRE MILANO SLIM LED

Diameter	System power	Luminous flux of luminaire	Colour temperature	Light control	Notes	Ref. n°
430 mm	13 W	1800 lm	4000 K	DALI		1 2004.2504
430 mm	13 W	1720 lm	3000 K	DALI		1 2004.2503
430 mm	22 W	3200 lm	4000 K	DALI		1 2004.2506
430 mm	22 W	3050 lm	3000 K	DALI		1 2004.2505
430 mm	24 W	3200 lm	4000 K	DALI	with emergency unit	1 2004.3869
430 mm	24 W	3050 lm	3000 K	DALI	with emergency unit	1 2004.3868
430 mm	23 W	3200 lm	4000K	MyLights Remote Casambi		1 2006.0632
430 mm	23 W	3050 lm	3000K	MyLights Remote Casambi		1 2006.0631
530 mm	17 W	2700 lm	4000 K	DALI		2 2004.2508
530 mm	17 W	2600 lm	3000 K	DALI		2 2004.2507
530 mm	33 W	4750 lm	2700-6500 K	MyLights Remote Casambi	MyLights Tunable	2 2004.2509
530 mm	34 W	5000 lm	4000 K	DALI		2 2004.2511
530 mm	34 W	4800 lm	3000 K	DALI		2 2004.2510
530 mm	36 W	5000 lm	4000 K	DALI	with emergency unit	2 2004.3871
530 mm	36 W	4800 lm	3000 K	DALI	with emergency unit	2 2004.3870
680 mm	35 W	5600 lm	4000 K	DALI		3 2004.2513
680 mm	35 W	5400 lm	3000 K	DALI		3 2004.2512
680 mm	48 W	7200 lm	4000 K	DALI	with emergency unit	3 2004.3873
680 mm	48 W	6900 lm	3000 K	DALI	with emergency unit	3 2004.3872
680 mm	60 W	9400 lm	4000 K	DALI		3 2004.2515
680 mm	60 W	9000 lm	3000 K	DALI		3 2004.2514


MOUNTING SET

WITH THREE MOUNTING POINTS

 for pendant mounting, without cable, $L_{\max} = 3 \text{ m}$ can be shortened on site


Notes	Ref. n°
3000 mm	1000.3193


MOUNTING SET

3 SUSPENSION CABLES PER MOUNTING POINT

 for pendant mounting, without cable, $L_{\max} = 3 \text{ m}$ can be shortened on site

Notes	Ref. n°
3000 mm	1000.3196


CABLE SET

for pendant mounting

Notes	Ref. n°
3 poles, 3000 mm, for MyLights Remote	1008.1440
5 poles, 3000 mm, DALI	1008.1445


PLUG & PLAY FLEX SENSOR

 compatible with MyLights Remote Casambi
 $\varnothing = 40 \text{ mm}$, $L = 60 \text{ mm}$

Notes	Ref. n°
white	2004.9947
black	2004.9946


MYLIGHTS SWITCH

compatible with MyLights Remote Casambi

Notes	Ref. n°
white	1022.0941
black	1022.0942